



RoHS

| REV. | REVISION RECORD | DATE | REV | REVISION RECORD | DATE |
|------|-----------------|------|-----|-----------------|------|
| A    |                 |      | C   |                 |      |
| B    |                 |      | D   |                 |      |

| NAME   | LS磁环盖                             | MATERIAL     | PET-FR530   | SCALE        | 3:1            | ANGLE       | $\pm 1^\circ$ |
|--|-----------------------------------|--------------|---|--------------|----------------|-------------|---------------|
| DRAWING NO.  | HX B004B                          | PIN MATERIAL |   | UNIT         | m/m            | REV.        | 00            |
|  <b>东莞市华欣塑胶制品有限公司</b><br>DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD.<br>TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111<br>http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com | TOLERANCE OF PIN PITCH $\pm 0.20$ |              |  |              | UL REC. : 94V0 |             |               |
|  | PIN TENSION LOAD kg MIN           |              | TOLERANCE: $0 < L \leq 4: \pm 0.1$ $4 < L \leq 16: \pm 0.2$ $16 < L \leq 63: \pm 0.3$ |              |                |             |               |
|  | DRAWN & DRAFTED BY                | LIN HUA JING | CHECKED & APPROVED BY   | LIN GUO PING | DATE:          | MAR 28 2005 |               |