



備註說明:

1. 材質: PM-9820
2. 強度要求: 1.80kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 焊錫溫度: 450° ±10° 3SEC
5. 拉力: 焊後拉力 1.50kg MIN
6. 模具狀況: 正式模

客户确认
签回

RoHS
HF

| | | | | | |
|------|-----------------|------|-----|-----------------|------|
| REV. | REVISION RECORD | DATE | REV | REVISION RECORD | DATE |
| 01 | | | 03 | | |
| 02 | | | 04 | | |

| | | | | | | | |
|-------------|---------------|--------------|---------|-------|-----|-------|-----|
| NAME | EE-1916 (10P) | MATERIAL | PM-9820 | SCALE | 1:1 | ANGLE | ±1° |
| DRAWING NO. | HX-1936 | PIN MATERIAL | CP WIRE | UNIT | m/m | REV. | 00 |



东莞市华欣塑胶制品有限公司
DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD.
TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111
http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com

| | | | |
|---------------------------------------------------|--------------|-----------------------|--------------|
| TOLERANCE OF PIN DIA ±0.05 | | — ⊕ — | |
| PIN TENSION LOAD 1.0 kg MIN | | UL REC. : 94V0 | |
| TOLERANCE: 0<L≤4: ±0.1 4<L≤16: ±0.2 16<L≤63: ±0.3 | | | |
| DRAWN & DRAFTED BY | LIN PENG FEI | CHECKED & APPROVED BY | LIN HUA JING |
| DATE: | | JUL 24 2025 | |