



備註說明:

1. PART NO. : HX-2212 樣品模
2. MATERIAL: PM-9820 MUST MEET UL94V-0
3. COLOR: BLACK
4. CORE TYPE: EE-22
5. MATERIAL OF PIN : 3/4H CP WIRE,  $\phi 0.80 \pm 0.05$
6. DIMENSION MARK :  $\triangle$  MAIN DIM.,  $\otimes$  SECOND DIM, OTHERWIRE ARE REFERENTIAL DIM..  
标示的  $\triangle$  为重要尺寸, 标示的  $\otimes$  为次要尺寸。
7. 強度要求: 1.80kg MIN
8. 耐壓要求: 4KV/1.5mA/1分鐘
9. 焊錫溫度:  $450^\circ \pm 10^\circ$  3SEC
10. 拉力: 焊後拉力 1.5kg MIN

客户确认		RoHS HF
签回		

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	EE-22 (12P)	MATERIAL	PM-9820	SCALE	1:1	ANGLE	$\pm 1^\circ$	
DRAWING NO.	HX-2212	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00	
 <b>东莞市华欣塑胶制品有限公司</b> DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO.,LTD. TEL:0769-86388088 86388188 86388288 FAX:0769-86388111 http://www.hxbobbin.com E-Mail:hxbobbin@vip.163.com		TOLERANCE OF PIN DIA $\pm 0.05$				PIN TENSION LOAD 1.5 kg MIN		UL REC. :94V0
		TOLERANCE: $0 < L \leq 4: \pm 0.1$ $4 < L \leq 16: \pm 0.2$ $16 < L \leq 63: \pm 0.3$				DRAWN & DRAFTED BY		LIN HUA JING