



備註說明:

1. PART NO. : HX-2313B 量產模
2. MATERIAL: PM-9630 MUST MEET UL94V-0
3. COLOR: BLACK
4. CORE TYPE: CR23/16.6
5. MATERIAL OF PIN :
6. 強度要求: 2.00kg MIN
7. 耐壓要求: 4KV/1.5mA/1分鐘
8. 焊錫溫度: 450° ±10° 3SEC
9. 成型後要烘烤, 烘烤條件150° 4小時
10. HX-2313A與HX-2313B匹配OK

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q
18.05	25.20	4.80	1.15	4.20	13.20	23.80	8.00	4.00	2.70	16.50	2.70	0.70	19.15	0.70	1.30	0.90
±0.3	±0.3	±0.2	±0.1	+0.1/-0.2	+0.2/-0.1	±0.3	±0.2	±0.1	±0.1	±0.3	±0.1	±0.1	±0.3	±0.1	±0.1	±0.1

客户确认
签回



REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	CR-23*16.6 CAP	MATERIAL	PM-9630	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX-2313B	PIN MATERIAL		UNIT	m/m	REV.	00
东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO.,LTD. TEL:0769-86388088 86388188 86388288 FAX:0769-86388111 http://www.hxbobbin.com E-Mail:hxbobbin@vip.163.com		TOLERANCE OF PIN DIA ±0.05				UL REC. :94V0	
		TOLERANCE: 0<L≤4: ±0.1 4<L≤16: ±0.2 16<L≤63: ±0.3		DRAWN & DRAFTED BY		CHECKED & APPROVED BY	
		LIN HUA JING					