



備註說明:

1. PART NO. : HX2310 量產模
2. MATERIAL: PM-9820 MUST MEET UL94V-0
3. COLOR: BLACK
4. CORE TYPE: EE-2319
5. MATERIAL OF PIN : 3/4H CP WIRE, SQ0.80±0.05
6. DIMENSION MARK : Δ MAIN DIM. , \otimes SECOND DIM, OTHERWIRE ARE REFERENTIAL DIM. .
标示的 Δ 为重要尺寸, 标示的 \otimes 为次要尺寸.
7. 強度要求: 1.80kg MIN
8. 耐壓要求: 4KV/1.5mA/1分鐘
9. 焊錫溫度: 450° ±10° 3SEC
10. 拉力: 焊後拉力 1.5kg MIN

客户确认
签回

RoHS
HF

| REV. | REVISION RECORD | DATE | REV | REVISION RECORD | DATE |
|------|------------------------------------|------------|-----|-----------------|------|
| 01 | 1. 側面凸點尺寸由1.0改為1.5 | 2014/04/21 | 03 | | |
| 02 | 1. 排距N尺寸由40.95±0.3改為40.95+0.1/-0.3 | 2014/07/07 | 04 | | |

| NAME | EE-2319 (9P) | MATERIAL | PM-9820 | SCALE | 1:1 | ANGLE | ±1° |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|-----------------------------------------------------------|---------|---------------------------------------------------|-----|-------------------|-----|
| DRAWING NO. | HX 2310 | PIN MATERIAL | CP WIRE | UNIT | m/m | REV. | 02 |
| 东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com | | TOLERANCE OF PIN DIA ±0.05 PIN TENSION LOAD 1.5 kg MIN | | TOLERANCE: 0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3 | | | |
| DRAWN & DRAFTED BY | | LIN HUA JING | | CHECKED & APPROVED BY | | DATE: MAR 10 2014 | |