



備註說明:

1. PART NO. : HX-2414 量產模
2. MATERIAL: PF-2736 MUST MEET UL94V-0
3. COLOR: BLACK
4. CORE TYPE: EE-2416
5. MATERIAL OF PIN : 3/4H CP WIRE, SQ0.80 ± 0.05
6. DIMENSION MARK : \triangle MAIN DIM. , \circledast SECOND DIM, OTHERWIRE ARE REFERENTIAL DIM. .

7. 強度要求: 2.00kg MIN
8. 耐壓要求: 4KV/1.5mA/1分鐘
9. 焊錫溫度: 450° ± 10° 3SEC
10. 拉力: 焊後拉力 2.0kg MIN

標示的 \triangle 为重要尺寸, 標示的 \circledast 为次要尺寸。

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	EE-2416 (8P)	MATERIAL	PF-2736	SCALE	1:1	ANGLE	± 1°
DRAWING NO.	HX-2414	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00



东莞市华欣塑胶制品有限公司
DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD.
TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111
http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com

TOLERANCE OF PIN DIA	± 0.05	
PIN TENSION LOAD	1.5 kg MIN	UL REC. : 94V0
TOLERANCE:	0 < L < 4 : ± 0.1 4 < L < 16 : ± 0.2 16 < L < 63 : ± 0.3	
DRAWN & DRAFTED BY	LIN HUA JING	CHECKED & APPROVED BY
DATE:	NOV 08 2014	