



備註說明:

1. 材質: T375HF
2. 強度要求: 1.80kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 焊錫溫度: 450° ±10° 3SEC
5. 拉力: 焊後拉力 1.53kg MIN
6. 模具狀況: 正式模

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01	1. 增加PIN針咬花外露	2014/03/01	03		
02			04		

NAME	EE-25 (8P)	MATERIAL	T375HF	SCALE	2:1	ANGLE	±1°
DRAWING NO.	HX 2501	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	01
		TOLERANCE OF PIN DIA ±0.05 PIN TENSION LOAD 1.5 kg MIN					
东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com		TOLERANCE: 0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3		UL REC.: 94V0			
DRAWN & DRAFTED BY		LIN HUA JING		CHECKED & APPROVED BY		DATE: MAY 04 2011	