



備註說明:

1. PART NO. : HX-3231 量產模
  2. MATERIAL: PM-9820 MUST MEET UL94V-0
  3. COLOR: BLACK
  4. CORE TYPE: EE-3217H
  5. MATERIAL OF PIN : 3/4H CP WIRE, SQ1.00±0.05
  6. DIMENSION MARK :  $\triangle$  MAIN DIM.,  $\otimes$  SECOND DIM., OTHERWIRE ARE REFERENTIAL DIM.
  7. 強度要求: 1.80kg MIN
  8. 拉力要求: 焊錫前2.00kg MIN  
焊錫後2.50kg MIN
- 标示的  $\triangle$  为重要尺寸, 标示的  $\otimes$  为次要尺寸。

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W
36.72	18.50	5.50	25.70	30.70	7.10	2.50	12.60	3.20	3.10	2.60	46.75	20.10	1.20	67.61	1.00	8.20	10.20	37.50	6.60	49.45	7.70	5.50
±0.3	±0.1	±0.1	±0.3	±0.2	±0.2	±0.1	±0.2	±0.1	±0.1	±0.1	±0.3	±0.3	±0.3	±0.3	±0.05	±0.2	±0.1	±0.3	±0.2	±0.3	±0.2	±0.2

客户确认		<b>RoHS</b> <b>HF</b>
签回		

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	EE-3217H(10P)	MATERIAL	PM-9820	SCALE	1/1	ANGLE	±1°	
DRAWING NO.	HX 3231	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00	
东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO.,LTD. TEL:0769-86388088 86388188 86388288 FAX:0769-86388111 http://www.hxbobbin.com E-Mail:hxbobbin@vip.163.com		TOLERANCE OF PIN DIA ±0.05				PIN TENSION LOAD kg MIN		UL REC. :94V0
		TOLERANCE:0<L<4:±0.1 4<L<16:±0.2 16<L<63:±0.3				DRAWN & DRAFTED BY		LIN HUA JING