



備註 (NOTE):

1. 材質: PM-9820
2. 強度要求: 0.50kg MIN
3. 耐壓要求: 4KV/1.5mA/1Min
4. 焊錫溫度: 450° ±10° 3SEC
5. 焊後拉力: 1.50kg MIN
6. 模具狀況: 量產模

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T
48.20	58.40	20.80	33.20	47.70	6.20	3.95	22.60	7.10	16.60	6.00	4.10	0.90	12.45	6.20	4.40	4.40	3.00	27.70	13.30
±0.3	±0.3	±0.1	±0.3	±0.3	±0.2	±0.1	±0.3	±0.2	±0.3	±0.2	±0.2	±0.05	±0.2	±0.2	±0.1	±0.2	±0.1	±0.3	±0.2

客户确认
签回



REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	EE-4115N(8P)	MATERIAL	PM-9820	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX 4021A	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00
东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO.,LTD. TEL:0769-86388088 86388188 86388288 FAX:0769-86388111 http://www.hxbobbin.com E-Mail:hxbobbin@vip.163.com		TOLERANCE OF PIN DIA ±0.05				UL REC. :94V0	
		TOLERANCE: 0<L≤4: ±0.1 4<L≤16: ±0.2 16<L≤63: ±0.3		DRAWN & DRAFTED BY		CHECKED & APPROVED BY	
		LIN HUA JING					