



備註說明1:

- PART NO. : HX 4022B 量产模
 - MATERIAL: PM-9820 MUST MEET UL94V-0
 - COLOR: BLACK
 - CORE TYPE: EE-4017H
 - MATERIAL OF PIN : 3/4H CP WIRE, SQ0.80±0.05
 - DIMENSION MARK : \triangle MAIN DIM., \otimes SECOND DIM., OTHER WIRE ARE REFERENTIAL DIM.
 - 強度要求: 頂部葉片1.20kg MIN 其他位置3.00kg MIN
 - 拉力要求: 焊錫前2.50kg MIN 焊錫後3.50kg MIN
- 标示的 \triangle 为重要尺寸, 标示的 \otimes 为次要尺寸。

組合圖

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	客户确认	RoHS HF
31.80	16.60	22.50	5.80	0.80	18.30	9.55	6.25	PL	12.85	7.50	3.10		31.85	3.50	24.50	5.00	19.40	59.80	签回		
±0.2	±0.1	±0.2	±0.1	±0.05	±0.3	±0.2	±0.2	±0.3	±0.2	±0.2	±0.1		±0.3	±0.1	±0.3	±0.2	±0.3	±0.3			

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	EE-4017H(4P)	MATERIAL	PM-9820	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX 4022B	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00
		TOLERANCE OF PIN DIA ±0.05				UL REC. :94V0	
东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO.,LTD. TEL:0769-86388088 86388188 86388288 FAX:0769-86388111 http://www.hxbobbin.com E-Mail:hxbobbin@vip.163.com		PIN TENSION LOAD kg MIN		TOLERANCE: 0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3		DATE: JAN 23 2016	
DRAWN & DRAFTED BY		LIN HUA JING		CHECKED & APPROVED BY			