



HX6002A與HX6002B組合圖

量產模

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	客户确认	RoHS HF
50.70	10.50	33.90	66.00	95.50	35.70	10.25	3.60	15.50	75.90	4.45	2.85	0.80	60.00	8.00	25.00	5.20	100.20	5.80	5.80	7.35	签回	
+0.20 -0.15	±0.15	±0.3	±0.3	±0.5	±0.3	±0.3	±0.1	±0.3	±0.3	±0.2	±0.2	±0.05	±0.3	±0.3	±0.3	±0.2	±0.5	±0.3	±0.3	+0.15 -0.20		
REV.	REVISION RECORD												DATE	REV	REVISION RECORD					DATE		
01	U尺寸由7.65+0.15/-0.2改為7.35+0.15/-0.2												2021/01/06	03								
02														04								

NAME	EE-6011 (8+4P)	MATERIAL	PM-9823	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX 6002A	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	01
 东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com		TOLERANCE OF PIN DIA ±0.05					
		PIN TENSION LOAD 1.5 kg MIN		UL REC. :94V0			
		TOLERANCE: 0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3					
DRAWN & DRAFTED BY		LIN HUA JING		CHECKED & APPROVED BY		DATE: SEP 01 2020	