



備註說明:

1. 材質: PBT-1403G6
2. 強度要求: 2.00kg MIN(中間葉片強度1.00kg MIN)
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 焊錫溫度: $420^{\circ} \pm 10^{\circ}$ 3SEC
5. 模具狀況: 量產模
6. 與HX-2404匹配OK

RoHS

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
A			C		
B			D		

NAME	ET-24	MATERIAL	PBT-1403G6	SCALE	2:1	ANGLE	$\pm 1^{\circ}$
DRAWING NO.	HX 2402	PIN MATERIAL		UNIT	m/m	REV.	00
 东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO.,LTD. TEL:0769-86388088 86388188 86388288 FAX:0769-86388111 http://www.hxbobbin.com E-Mail:hxbobbin@vip.163.com		TOLERANCE OF PIN PITCH ± 0.20		 UL REC. :94V0			
		PIN TENSION LOAD kg MIN				TOLERANCE: $0 < L \leq 4: \pm 0.1$ $4 < L \leq 16: \pm 0.2$ $16 < L \leq 63: \pm 0.3$	
DRAWN & DRAFTED BY		LIN HUA JING		CHECKED & APPROVED BY		LIN GUO PING	
				DATE:		OCT 05 2003	