



備註說明:

1. 材質: PM-9820
2. 強度要求: 1.80kg MIN,
3. 耐壓要求: 4KV/0.5mA/3S
4. 焊錫溫度: 400° ± 10° 2SEC
5. 拉力: 焊錫前0.60kg MIN, 焊錫後1.20kg MIN
6. 模具狀況: 量產模

A	B	C	D	E	F	G	H	I	J	K	L	M
5.70	1.60	6.50	1.50	3.20	5.00	2.00	3.20	0.60	8.00	1.10	7.00	3.30
±0.2	±0.1	±0.2	±0.1	±0.1	±0.2	±0.1	±0.3	±0.05	±0.2	±0.1	±0.2	±0.1

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	7.0*6.0BASE(2P)	MATERIAL	PM-9820	SCALE	4/1	ANGLE	± 1°
DRAWING NO.	HX B028	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00



东莞市华欣塑胶制品有限公司
DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO.,LTD.
TEL:0769-86388088 86388188 86388288 FAX:0769-86388111
http://www.hxbobbin.com E-Mail:hxbobbin@vip.163.com

TOLERANCE OF PIN DIA	±0.05	
PIN TENSION LOAD	kg MIN	UL REC. :94V0
TOLERANCE:	0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3	
DRAWN & DRAFTED BY	LIN HUA JING	CHECKED & APPROVED BY
DATE:	DEC 18 2010	