



備註說明:

1. 材質: T375HF
2. 強度要求: 2.50kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 焊錫溫度: $450^{\circ} \pm 10^{\circ}$ 3SEC
5. 拉力: 焊後拉力 1.53kg MIN
6. 模具狀況: 正式模

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	13*13BASE (6P)	MATERIAL	T375HF	SCALE	3:1	ANGLE	$\pm 1^{\circ}$
DRAWING NO.	HX-B038	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00
 东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO.,LTD. TEL:0769-86388088 86388188 86388288 FAX:0769-86388111 http://www.hxbobbin.com E-Mail:hxbobbin@vip.163.com		TOLERANCE OF PIN DIA ± 0.05					
		PIN TENSION LOAD 1.5 kg MIN				UL REC. :94V0	
		TOLERANCE: $0 < L \leq 4: \pm 0.1$ $4 < L \leq 16: \pm 0.2$ $16 < L \leq 63: \pm 0.3$					
DRAWN & DRAFTED BY		LIN HUA JING		CHECKED & APPROVED BY		DATE: AUG 29 2014	