



備註說明:

1. 材質: T375HF
2. 強度要求: 2.5kg MIN,
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 焊錫溫度: 450° ± 10° 3SEC
5. 拉力: 焊後拉力 1.53kg MIN
6. 模具狀況: 量產模

客户确认  
签回

RoHS  
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01	△ 定位柱子尺寸2.30改為2.05	2022/06/24	03		
02			04		

NAME	8x12 BASE (2P)	MATERIAL	T375HF	SCALE	1:1	ANGLE	± 1°	
DRAWING NO.	HX B050	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	01	
 <b>东莞市华欣塑胶制品有限公司</b> DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com		TOLERANCE OF PIN DIA ±0.05				PIN TENSION LOAD 1.0 kg MIN		UL REC. :94V0
		TOLERANCE: 0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3		DRAWN & DRAFTED BY		LIN HUA JING	CHECKED & APPROVED BY	