



備註說明:

1. 材質: T375HF
2. 強度要求: 2.00kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 焊錫溫度: 450° ± 10° 3SEC
5. 拉力: 焊前是1.0kg MIN, 焊後是1.5kg MIN
6. 模具狀況: 量產模



REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01	F尺寸1.00改為1.50	2020/02/21	03		
02			04		

NAME	BASE(4P)	MATERIAL	T375HF	SCALE	1:1	ANGLE	± 1°
DRAWING NO.	HX B054	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	01



东莞市华欣塑胶制品有限公司
 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD.
 TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111
 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com

TOLERANCE OF PIN PITCH ± 0.20		— ⊕ —	
PIN TENSION LOAD kg MIN		UL REC. : 94V0	
TOLERANCE: 0 < L < 4: ± 0.1 4 < L < 16: ± 0.2 16 < L < 63: ± 0.3			
DRAWN & DRAFTED BY	LIN HUA JING	CHECKED & APPROVED BY	LIN GUO PING
DATE:		NOV 25 2018	