



備註說明:

1. 材質: PM-9630
2. 強度要求: 1.80kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 焊錫溫度: 450° ±10° 3SEC
5. 拉力: 焊前是1.0kg MIN, 焊後是1.5kg MIN
6. 模具狀況: 量產模



REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01	F尺寸線徑1.00改為0.80	2019/11/28	03		
02			04		

NAME	T18 BASE(4P)	MATERIAL	PM-9630	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX B059	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	01
<p>东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO.,LTD. TEL:0769-86388088 86388188 86388288 FAX:0769-86388111 http://www.hxbobbin.com E-Mail:hxbobbin@vip.163.com</p>		TOLERANCE OF PIN PITCH ±0.20				UL REC. :94V0	
		PIN TENSION LOAD kg MIN		TOLERANCE: 0<L≤4: ±0.1 4<L≤16: ±0.2 16<L≤63: ±0.3			
DRAWN & DRAFTED BY		LIN HUA JING		CHECKED & APPROVED BY		DATE: NOV 20 2019	