



紅色線條是合模線位置

進膠口位置

備註說明:

1. 強度要求: 1.50kg MIN
2. 耐壓要求: 4KV/1.5mA/1分鐘
3. 模具狀況: 量产模

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01	△ 凸點刪除	2020/04/25	03		
02			04		

NAME	T-21 BASE	MATERIAL	PM-9823	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX B071	PIN MATERIAL		UNIT	m/m	REV.	01
 <p>东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com</p>	TOLERANCE OF PIN DIA ±0.05		— ⊕ —		UL REC. :94V0		
	PIN TENSION LOAD kg MIN		TOLERANCE: 0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3				
	DRAWN & DRAFTED BY	LIN HUA JING	CHECKED & APPROVED BY		DATE:	JAN 08 2020	