



備註說明:

1. 材質: PM-9630
2. 強度要求: 2.00kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 焊錫溫度: 450° ±10° 3SEC
5. 拉力: 焊後1.5kg MIN
6. 模具狀況: 樣品模

客户确认		RoHS HF
签回		

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	T16-4P-BASE	MATERIAL	PM-9630	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX-B092	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00


东莞市华欣塑胶制品有限公司
 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO.,LTD.
 TEL:0769-86388088 86388188 86388288 FAX:0769-86388111
 http://www.hxbobbin.com E-Mail:hxbobbin@vip.163.com

TOLERANCE OF PIN DIA ±0.05		
PIN TENSION LOAD kg MIN		UL REC. :94V0
TOLERANCE: 0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3		
DRAWN & DRAFTED BY	LIN HUA JING	CHECKED & APPROVED BY
DATE:		MAR 02 2021