



備註:

1. 焊錫溫度: $450^{\circ} \pm 10^{\circ}$ 3SEC
2. 焊錫前拉力: 1.0kgf MIN
3. 焊錫後拉力: 1.50kgf MIN
4. 阻燃測試: 燃燒10SEC, 在10SEC內自然熄滅。
5. 耐壓測試: 4.5KV, 0.5mA, 3SEC
6. 強度: 1.5kgf MIN
7. 量產模

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	T-14 BASE (4P)	MATERIAL	T375HF	SCALE	1:1	ANGLE	$\pm 1^{\circ}$
DRAWING NO.	HX B129A	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00
 东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO.,LTD. TEL:0769-86388088 86388188 86388288 FAX:0769-86388111 http://www.hxbobbin.com E-Mail:hxbobbin@vip.163.com		TOLERANCE OF PIN DIA ± 0.05					
		PIN TENSION LOAD kg MIN				UL REC. :94V0	
		TOLERANCE: $0 < L < 4: \pm 0.1$ $4 < L < 16: \pm 0.2$ $16 < L < 63: \pm 0.3$					
DRAWN & DRAFTED BY		LIN HUA JING		CHECKED & APPROVED BY		DATE: DEC 19 2024	