



備註:

1. 阻燃測試: 燃燒10SEC, 在10SEC內自然熄滅。
2. 耐壓測試: 4.5KV, 0.5mA, 3SEC
3. 強度: 1.5kgf MIN
4. 量產模

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	T-14 COVER	MATERIAL	PET-FR530 (NC)	SCALE	1:1	ANGLE	$\pm 1^\circ$
DRAWING NO.	HX B129B	PIN MATERIAL		UNIT	m/m	REV.	00
 <p>东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com</p>	TOLERANCE OF PIN DIA ± 0.05						
	PIN TENSION LOAD kg MIN				UL REC. :94V0		
	TOLERANCE: $0 < L \leq 4: \pm 0.1$ $4 < L \leq 16: \pm 0.2$ $16 < L \leq 63: \pm 0.3$						
DRAWN & DRAFTED BY	LIN HUA JING	CHECKED & APPROVED BY		DATE:	DEC 19 2024		