



備註說明:

1. 材質: PM-9630
2. 強度要求: 1.8kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 焊錫溫度: 450° ± 10° 3SEC
5. 焊後拉力: 1.5kgf MIN
6. 模具狀況: 樣品模

客户确认  
签回

RoHS  
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	PS-2632-1S BASE-B(2P)	MATERIAL	PM-9630	SCALE	1:1	ANGLE	± 1°
DRAWING NO.	HX-B139	PIN MATERIAL		UNIT	m/m	REV.	00
 东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com	TOLERANCE OF PIN DIA		±0.05				
	PIN TENSION LOAD		kg MIN			UL REC. :94V0	
	TOLERANCE:		0<L<4: ±0.1	4<L<16: ±0.2	16<L<63: ±0.3		
DRAWN & DRAFTED BY	LIN HUA JING	CHECKED & APPROVED BY		DATE:	APR 11 2025		