


进胶口



備註:

1. 焊錫溫度: 450° ±10° 3SEC
2. 焊錫前拉力: 1.0kgf MIN
3. 焊錫後拉力: 1.50kgf MIN
4. 阻燃測試: 燃燒10SEC, 在10SEC內自然熄滅。
5. 耐壓測試: 4.5KV, 0.5mA, 3SEC
6. 強度: 1.0kgf MIN
7. 量產模

客户确认  
签回

RoHS  
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	SQ-2018 (4P)	MATERIAL	T375HF	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX-B140	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00
 <p>东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO.,LTD. TEL:0769-86388088 86388188 86388288 FAX:0769-86388111 http://www.hxbobbin.com E-Mail:hxbobbin@vip.163.com</p>	TOLERANCE OF PIN DIA ±0.05		—⊕—				
	PIN TENSION LOAD 1.0 kg MIN		UL REC. :94V0				
	TOLERANCE: 0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3						
DRAWN & DRAFTED BY	LIN HUA JING	CHECKED & APPROVED BY		DATE:	MAY 28 2025		