



備註說明:

1. 材質: PM-9630
2. 強度要求: 1.5kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 模具狀況: 樣品模

客户确认
簽回

RoHS
HF

| REV. | REVISION RECORD | DATE | REV | REVISION RECORD | DATE |
|------|-----------------|------|-----|-----------------|------|
| 01 | | | 03 | | |
| 02 | | | 04 | | |

| NAME | PQ-42 BASE | MATERIAL | PM-9630 | SCALE | 1:1 | ANGLE | ±1° |
|--|--------------|---|--------------|---|-------------|---------------|-----|
| DRAWING NO. | HX-B147 | PIN MATERIAL | | UNIT | m/m | REV. | 00 |
|  东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO.,LTD. TEL:0769-86388088 86388188 86388288 FAX:0769-86388111 http://www.hxbobbin.com E-Mail:hxbobbin@vip.163.com | | TOLERANCE OF PIN DIA ±0.05 | |  | | | |
| | | PIN TENSION LOAD 1.0 kg MIN | | | | UL REC. :94V0 | |
| | | TOLERANCE: 0<L≤4: ±0.1 4<L≤16: ±0.2 16<L≤63: ±0.3 | | | | | |
| DRAWN & DRAFTED BY | LIN PENG FEI | CHECKED & APPROVED BY | LIN HUA JING | DATE: | SEP 25 2025 | | |