



备注:

1. 电镀要求:2-3UM铜底,5-8UM纯锡.

RoHS  
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
A			C		
B			D		

NAME	S-58-N16P-HX	MATERIAL	PPS-R7	SCALE	2:1	ANGLE	$\pm 1^\circ$
DRAWING NO.	HX SC002	PIN MATERIAL	C5191	UNIT	m/m	REV.	00
 <b>东莞市华欣塑胶制品有限公司</b> DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com		TOLERANCE OF PIN PITCH $\pm 0.05$		 UL REC.: 94V0			
		PIN TENSION LOAD 0.8 kg MIN					
		TOLERANCE: 0<L<1.5: $\pm 0.05$ 1.5<L<4: $\pm 0.1$ 4<L<16: $\pm 0.15$ 16<L<63: $\pm 0.25$					
DRAWN & DRAFTED BY		LIN HUA JING		CHECKED & APPROVED BY		LIN GUO PING	
				DATE:		AUG 29 2007	