



備註說明:

1. 材質: PM-9630
2. 強度要求: 1.50kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 焊錫溫度: 450° ± 10° 3SEC
5. 拉力: 焊後拉力 2.00kg MIN
6. 模具狀況: 正式模

客户确认  
签回

RoHS  
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01	1. C尺寸由8.60改為9.20, D尺寸由3.00改為3.60, H尺寸由2.30改為2.70, 2. BASE凸點高度由0.70改為0.90, PIN孔深度由1.75改為2.30	2014/02/26	03		
02			04		

NAME	EE-8.3(4P)	MATERIAL	PM-9630	SCALE	3/1	ANGLE	± 1°
DRAWING NO.	HX-0821	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	01
		TOLERANCE OF PIN DIA ±0.05 PIN TENSION LOAD 2.0 kg MIN					
东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com		TOLERANCE: 0<L≤4: ±0.1 4<L≤16: ±0.2 16<L≤63: ±0.3		DATE: JUL 23 2013			
DRAWN & DRAFTED BY		LIN HUA JING		CHECKED & APPROVED BY			