



備註說明:

- 強度要求: 2.0kg MIN.
- PIN徑: PIN1-6, 9, 10是方0.50;
PIN7-8是方0.60.
- 焊前拉力: PIN1-8拉力是 1.0kg MIN;
PIN9-10拉力是0.6kg MIN.
- 焊後拉力: PIN1-8拉力是 2.4kg MIN;
PIN9-10拉力是1.0kg MIN.
- 模具狀況: 正式模。

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01	△ 尺寸12.70改為13.10(頂部葉片加高0.40mm)	2025/03/10	03		
02			04		

NAME	EE-13 (8+2P)	MATERIAL	T200HF	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX-1347	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	01
<p>东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com</p>		TOLERANCE OF PIN DIA ±0.05				UL REC.: 94V0	
		TOLERANCE: 0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3		DRAWN & DRAFTED BY		CHECKED & APPROVED BY	
		LIN HUA JING					