



備註說明:

1. 材質: PM-9820
2. 強度要求: 其他位置1.5kg MIN, 另凸點1.30kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 焊錫溫度: 450° ±10° 3SEC
5. 拉力: 焊後拉力 1.53kg MIN
6. 模具狀況: 量產模

客户确认		RoHS HF
签回		

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	EE-16 (10P)	MATERIAL	PM-9820	SCALE	2:1	ANGLE	±1°
DRAWING NO.	HX-1632	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00



东莞市华欣塑胶制品有限公司
DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD.
TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111
http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com

TOLERANCE OF PIN DIA	±0.05	
PIN TENSION LOAD	1.2 kg MIN	UL REC. :94V0
TOLERANCE:	0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3	
DRAWN & DRAFTED BY	LIN HUA JING	CHECKED & APPROVED BY
DATE:	DEC 20 2013	