



備註說明:

1. 材質: PM-9820
2. 強度要求: 其他位置1.8kg MIN, 另凸點1.30kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 焊錫溫度: 450° ±10° 3SEC
5. 拉力: 焊後拉力 1.53kg MIN
6. 模具狀況: 量產模
7. PIN腳規格: 空3, 7腳

客户确认  
签回

RoHS  
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01	△ 頂部葉片加厚0.20, 尺寸由0.90改為1.10	2024/06/25	03		
02			04		

NAME	EE-16 (8P)	MATERIAL	PM-9820	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX-1633	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	01
		TOLERANCE OF PIN DIA ±0.05 PIN TENSION LOAD 1.0 kg MIN		UL REC. :94V0			
东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO.,LTD. TEL:0769-86388088 86388188 86388288 FAX:0769-86388111 http://www.hxbobbin.com E-Mail:hxbobbin@vip.163.com		TOLERANCE: 0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3		DRAWN & DRAFTED BY LIN HUA JING CHECKED & APPROVED BY DATE: JUN 25 2024			