


備註說明:

- 1. 材質: PM-9820
- 2. U型PIN: CP WIRE,  $\varnothing 1.00 \pm 0.05$   
 Ni: 1-2um MIN; Sn: 5-7um MIN (霧錫)  
 PIN: CP WIRE 3/4H SQ0.64  $\pm 0.05$   
 Ni: 1-2um MIN; Sn: 5-7um MIN (霧錫)

客户确认  
 签回

RoHS  
 HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	EE-16 (2+2P)	MATERIAL	PM-9820	SCALE	1:1	ANGLE	$\pm 1^\circ$	
DRAWING NO.	HX 1643	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00	
 东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com		TOLERANCE OF PIN DIA $\pm 0.05$				PIN TENSION LOAD 1.0 kg MIN		UL REC. : 94V0
		TOLERANCE: $0 < L < 4: \pm 0.1$ $4 < L < 16: \pm 0.2$ $16 < L < 63: \pm 0.3$		DRAWN & DRAFTED BY		LIN HUA JING	CHECKED & APPROVED BY	