



備註說明:

1. 模具狀況: 正式模
2. 強度要求: 2.00kg MIN(不含中間葉片)
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 值PIN方式: 圓孔方PIN

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	EED-1510 (6P)	MATERIAL	LCP-6130LX	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX 1511	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00
		TOLERANCE OF PIN DIA ±0.05 PIN TENSION LOAD 1.0 kg MIN					
东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO.,LTD. TEL:0769-86388088 86388188 86388288 FAX:0769-86388111 http://www.hxbobbin.com E-Mail:hxbobbin@vip.163.com		TOLERANCE: 0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3		UL REC.: 94V0			
DRAWN & DRAFTED BY		LIN HUA JING		CHECKED & APPROVED BY		DATE: OCT 31 2012	