



備註說明:

1. 材質: PM-9630
2. 強度要求: 1.30kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 焊錫溫度: 450° ±10° 3SEC
5. 拉力: 焊後拉力 1.5kg MIN
6. 模具狀況: 正式模

客户确认
 签回
 RoHS
 HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01	1. 第一個過線槽改為45°角出口, 線槽寬度0.95改為0.90+0.02/-0; 2. U尺寸22.60+0/-0.3改為22.60+0.4/-0.2	2012/12/23	03	1. B尺寸11.10+0.1/-0.2改為11.10+0.3/-0, E尺寸5.40±0.2改為5.20+0/-0.2, L尺寸4.00±0.1改為4.00±0.05	2014/01/21
02	1. PIN6邊PIN台BASE填平厚度為3.50mm	2013/01/04	04		

NAME	EED-1510(6P)	MATERIAL	PM-9630	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX-1512	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	03
东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com		TOLERANCE OF PIN DIA ±0.05		UL REC.: 94V0			
		PIN TENSION LOAD 1.0 kg MIN					
		TOLERANCE: 0<L≤4: ±0.1 4<L≤16: ±0.2 16<L≤63: ±0.3					
DRAWN & DRAFTED BY		LIN HUA JING	CHECKED & APPROVED BY		DATE: OCT 23 2012		