



備註說明:

1. 模具狀況: 正式模
2. 強度要求: 1.30kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘

N1	EED-1510V-6P (P1.8)	1.80±0.2
N2	EED-1510V-6P (P2.1)	2.10±0.2

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01	1. 第一個過線槽改為45°角出口, 線槽寬度0.95改為0.90+0.02/-0; 2. U尺寸22.60+0/-0.3改為22.60+0.4/-0.2	2012/12/23	03		
02	1. PIN6邊PIN台BASE填平厚度為3.50mm	2013/01/04	04		

NAME	EED-1510 (6P)	MATERIAL	PM-9630	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX 1515	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	02
东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com		TOLERANCE OF PIN DIA ±0.05					
		PIN TENSION LOAD 1.0 kg MIN		UL REC. :94V0			
		TOLERANCE: 0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3					
DRAWN & DRAFTED BY		LIN HUA JING		CHECKED & APPROVED BY		DATE: OCT 23 2012	