


備註說明:

- 1. 材質: PM-9630
- 2. 強度要求: 1.20kg MIN
- 3. 耐壓要求: 4KV/1.5mA/1分鐘
- 4. 焊錫溫度: 450° ± 10° 3SEC
- 5. 焊錫後拉力: 1.50kg MIN
- 6. 模具狀況: 量產模
- 7. 吸塑包裝
- 8. PIN切面不可露銅
- 9. PIN平貼度0.15mm MAX

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	EP-13 (10P)	MATERIAL	PM-9630	SCALE	1:1	ANGLE	± 1°
DRAWING NO.	HX-1348	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00
 东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO.,LTD. TEL:0769-86388088 86388188 86388288 FAX:0769-86388111 http://www.hxbobbin.com E-Mail:hxbobbin@vip.163.com		TOLERANCE OF PIN DIA ±0.05				PIN TENSION LOAD 1.0 kg MIN	
		TOLERANCE: 0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3		UL REC. :94V0		DATE: AUG 11 2025	
DRAWN & DRAFTED BY		LIN HUA JING		CHECKED & APPROVED BY			