



備註說明:

1. 模具狀況: 正式模
2. 強度要求: 中間葉片1.0kg MIN, 其他部位1.5kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01	1. A, B, C, D, J尺寸由4.5, 3.3, 4.5, 3.3, 1.5改為4.6, 3.0, 4.6, 3.0, 2.0	2013/01/19	03		
02	1. 中間葉片下部開一個缺口	2013/03/08	04		

NAME	UU-9.8(4P)	MATERIAL	T375HF	SCALE	2:1	ANGLE	±1°
DRAWING NO.	HX 0901	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	02
		TOLERANCE OF PIN DIA ±0.05 PIN TENSION LOAD 1.0 kg MIN					
东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com		TOLERANCE: 0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3		DRAWN & DRAFTED BY LIN HUA JING CHECKED & APPROVED BY DATE: AUG 07 2003			