



PIN咬花外露 (Textured exposed)  
DETAIL B (2:1)

備註 (NOTE):

- PART NO. : HX-1638
- MATERIAL: T375HF MUST MEET UL94V-0
- COLOR: BLACK
- CORE TYPE: UU-16
- MATERIAL OF PIN : 3/4H CP WIRE, 圓0.70±0.05
- DIMENSION MARK :  $\triangle$  MAIN DIM.,  $\otimes$  SECOND DIM, OTHERWIRE ARE REFERENTIAL DIM. .  
标示的  $\triangle$  为重要尺寸, 标示的  $\otimes$  为次要尺寸。

- 強度要求 (Strength requirement): 2.50kg MIN; 中間葉片為 (Intermediate blande for): 1.0kg MIN
- 耐壓要求 (HI-POT requirements): 4KV/1.5mA/1Min
- 焊錫溫度 (Soldering temperature): 450° ±10° 3SEC
- 拉力 (Pull): 焊後拉力 (After welding tension) 1.8kg MIN
- 模具狀況 (The mould status): 正式模 (Formal mold)

此葉片強度1.00kg MIN

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q
7.80	6.40	4.90	6.30	18.20	17.50	17.50	19.70	18.20	1.50	6.30	13.00	11.60	10.00		13.00	0.70
±0.2	±0.1	+0.1/-0.05	±0.2	±0.3	±0.3	±0.3	±0.3	±0.3	±0.1	±0.1	±0.2	±0.1	±0.2		±0.2	±0.05

R	S	T	U	V	W	X
9.30	10.00	0.80	0.95	17.50	1.85	17.20
±0.2	±0.2	±0.05	±0.05	±0.3	+0.1/-0.05	±0.3
客户确认						RoHS HF
签回						

REV.	REVISION RECORD					DATE	REV	REVISION RECORD					DATE
01	T, U, W尺寸0.70, 1.00, 1.90改為0.80, 0.95, 1.85					2016/06/15	03						
02							04						

NAME	UU-16 (4P)	MATERIAL	T375HF	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX-1638	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	01
		TOLERANCE OF PIN DIA ±0.05				UL REC. : 94V0	
东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com		TOLERANCE: 0<L≤4: ±0.1 4<L≤16: ±0.2 16<L≤63: ±0.3					
DRAWN & DRAFTED BY		LIN HUA JING		CHECKED & APPROVED BY		DATE: JUL 29 2015	